



SATFIND 406 II[™] SURVIVAL EPIRB

406 EPIRB

Product No.: S1110
Product No.: S1115

SATFIND II CAT 1
SATFIND II CAT 2



Enjoy safety and security with the worlds smallest 406 MHz EPIRB that meets all regulations and is fully approved worldwide. Life saving technology is now readily available. Unleash the power of the SATFIND 406 II[™] 406 MHz EPIRB with GPS interface and turn that life threatening situation into a successful rescue story.

The SATFIND 406 II[™] Category 1 EPIRB is fully enclosed in a high density, UV stabilized polyethylene bracket with hydrostatic release that withstands extremely abusive environments, while the Category 2 Low Pro₂ bracket offers bulkhead and rail mounting options.

Patented proprietary electronics delivers greater frequency stability for

the most accurate position through the LEOSAR satellites.

Be Responsible.

Be Prepared.

Be Safe.



ACR Electronics, Inc.
5757 Ravenswood Rd
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: + 1(954) 961-4403
www.acrelectronics.com



ACR Electronics, Inc. is registered by UL to ISO 9001:2000



Did you know...

406 MHz technology has been around since 1982 and is credited with saving over 20,300 lives worldwide.

In 2006, of the 105 incidents in the US, 272 people are alive thanks to the SARSAT system.

Registration...

It is mandatory that you register your EPIRB. It's fast, easy and free.

www.406registration.com

When activated, the unique identification code in your EPIRB is linked to the registration database. This way authorities can retrieve valuable information about you and your trip.

Responsible Use...

EPIRBs are a satellite signaling device of last resort, for use when all other means of self rescue have been exhausted, where the situation is grave, and imminent loss of life, limb, eyesight, or valuable property will occur without assistance.

Product Details

World's smallest 406 MHz EPIRB that meets all regulation and is fully approved worldwide.

Automatically activated when out of bracket and in the water, or manually activated.

Audio/visual indicators of active transmission.

Floats upright with high visibility built-in strobe.

Category 1: Fully enclosed, high density, UV stabilized polyethylene bracket with hydrostatic release. Withstands extremely abusive environments. Hydrostatic release automatically deploys EPIRB if vessel sinks to approximately 4m (13ft.).

Category 2: Universal Low Pro2 bracket. Includes bulkhead and rail mount option.

Transmits on 406 MHz (COSPAS-SARSAT) with your registered, digitally coded distress signal, and 121.5 MHz (SAR homing frequency).

Beacon Size:	14.5 x 4.25 x 3.62" (36.8 x 10.8 x 9.2 cm)
Beacon Weight:	1.9 lbs. (.86 kg)
Operational Life:	In excess of 48 hours at -40°C (-40°F) longer in higher ambient temperatures
Battery Type:	Lithium, 5 year replacement life (11 year storage)
Storage Temp:	-50°C to +70°C (-58°F to +158°F)
Modulation:	AM
Radiated Power:	5 watts ± 2dB (406MHz) / 50 mW ± 3dB (121.5 MHz)
Material:	High impact polycarbonate blend case/ polyethylene bracket
Color:	High vis yellow
Deployment:	Category 1: Automatic, hydrostatic release Category 2: Manual
Accessories:	Category 1: Hydrostatic Release Kit (P/N 9490) Battery, Class 1: P/N 1096
Waterproof:	10m (33ft.)
Certification:	Approved by COSPAS-SARSAT, FCC, USCG, complies with GMDSS, MED
Limited Warranty:	5 years